

PRIVATE AND CONFIDENTIAL

FB/100-FB/200-FGA/200 MEASUREMENT CHART

Customer _____ Date _____

Important it is essential that the measurements you record are as accurate as possible. A high degree of care and attention must be given to this task. Take plenty of time, repeating the measurement procedure until you are confident you are recording consistent and accurate values. **These ranges of belt sets are of a riveted construction and are not adjustable.** Whilst small errors are not difficult to correct, major ones will invariably incur higher cost. An ordinary fabric or plastic tape measure of the type used for dressmaking is best for taking the measurements. You should aim at a tight rather than a loose fit, as experience shows a tight fit is far more comfortable than a loose one, which may also degrade effectiveness.

The subject should stand erect with their feet about twenty-four inches (600 mm) apart and hands placed on back of their head while all the measurements are taken. **These Belt sets are designed to fit into waist and cannot be worn on the hips like some fashionable jeans, trousers and skirts. The main reference point for all measurements is the bottom edge of the waistband,** so it is of crucial importance that it is measured to fit the **waist**. For the person with a fuller or waistless figure, the Belt set will only be secure if the waistband is smaller than the circumference of the hips. Measurement **M** should be used to determine this, and the degree of discomfort that results. **All measurements must be taken next to the skin.**

	Description	Inches	Cms	N/A
A	Waist normal	A=	A=	
B	Waist controlled (take a deep breath and pull in to make it as small as possible)	B=	B=	
C	Front waist down between the legs to the start of the labia lips	C=	C=	
D	Front waist down between the legs to the end of the labia lips	D=	D=	
I	Waist front between legs to anus	I=	I=	
J	Waist front between legs and buttocks to rear waist	J=	J=	
K	Waist front between legs and over buttocks to rear waist	K=	K=	
L	Waist rear between buttocks to anus	L=	L=	
M	Waist measurement using one inch wide belt.	M=	M=	
N	Hips circumference	N=	N=	
P	Body height.	P=	P=	

- C. Fasten a one-inch wide belt around the waist, and from the **bottom edge** of the belt at front centre, measure down to the start of the labia lips.
- D. From the **bottom edge** of the belt at front centre, measure down to the end of the labia lips.
- I. From the same point, measure down between the legs to the anus, keeping as straight as possible, **This is a very important measurement** for the sake of accuracy it is worth repeating several times. The subject must maintain an upright position during this procedure.
- J. With the belt still in position, find the centre back of the waist and mark it. Make two further marks; one 3 inches to the right of the centre, and another 3 inches to the left. By measuring from the centre back mark find the front centre of the waist and mark it. At the front centre, measure from the **bottom edge** of the belt down between the legs and up over the buttocks to the right hand mark at the rear waist, **bottom edge**. Repeat this procedure to the left-hand mark. This second measurement should be the same and serves as double check. Make sure the measuring tape stays flat and snug against the skin all the way, taking the most direct route possible. Exercise care with these measurements.
- K. With the belt still in place, measure from the **bottom edge** front centre to the **bottom edge** rear centre. Make sure the tape fits snugly up between the buttocks.
- L. From the **bottom edge** of the belt rear centre waist measure down between the buttocks to the anus.
- M. Adjust the belt to the smallest circumference at which you feel you could wear it and mark the position. Do not be tempted to settle for a nice comfortable fit, aim at a tight rather than a loose fit. Remove the belt, lay it out flat and measure from the end to the reference mark to determine the length. **The waistband will be made to this measurement.** A and B are used to provide a comparative check.

MEASURING INSTRUCTIONS

With the belt still in position around the waist, fit another belt or similar around one of the thighs at the desired position (6" above the knee is a typical choice, lower than this is not very practical).

Measure from the bottom edge of the waist belt at the side, down over the hip to the top edge of the thigh belt keeping the tape in contact to follow the hip profile. Mark the thigh belt before you remove it, lay it out flat and measure from the end to the reference mark to determine the circumference. Repeat this procedure with the other thigh in case there is any significant difference.

	Inches	Cms
Right Thigh Circumference		
Left Thigh Circumference		
Side Chain Length		

FITTING INSTRUCTIONS FOR TYPE FB/100 BELT SET

Important Note. Due to the type of belt and the fact that it has not been fitted by Tollyboy Products, it is not possible to provide an anatomically correct to the wearer pre-shape. However the steel is tempered to render it easy to manipulate by hand to effect a fitting shape. The steel remains hardened with no loss of security.

The locking system supplied with the belt sets is unique to Tollyboy products, it offers very high security but is simple in concept. You will find it easy to use once you become familiar with the system. The first task is to unlock the waistband; the procedure for this is as follows.

Enter the appropriate key into the lock and turn anti-clockwise whilst maintaining a light inwards pressure. Continue to turn the key and you will observe that the lock is unscrewing revealing two anti-turn guide pins. Unscrew the lock till it disengages completely, approximately 5 to 7 turns will be required. Make sure you keep the lock parallel on the last two turns when almost clear of the guide pins, and avoid the tendency for it becoming cross-threaded.

The wearer should be naked to facilitate fitting, the belt is designed to fit next to the skin and no attempt should be made to wear it over under garments. Spring open the waistband just sufficient to slip it on to the waist and centralise it so that the guard hangs down the back and centrally between the legs. Close the waistband by engaging it's locking spigot and guide pins; it will be easier to do this if the wearer stretches her hands above her head in an attempt to reduce the waist to minimum. The waist band should be a snug fit on the waist and be in contact all the way round. This is where a degree of reshaping may be required but in any case you will find that it will assume the shape of the waist after a reasonable period of wear. Make sure the wearer is stood with her legs well apart, swing the guard up between the legs and engage the top end with the locking spigot and guide pins. **A word of warning**, do not make any attempt to force the joint together by using the locks screwing action. If you have any difficulty in getting the waist band and guard to seat correctly, you may find that if the wearer lays flat on her back at this juncture it will alleviate the problem. This position allows the body mass to settle back into the waistband easing any pressure at the joint. When you are satisfied that the joint is aligned and seated correctly you are then ready to fit the lock. You will observe that the lock has a small T on the outer edge, **it is important that the lock is always fitted with this flat at the top**. Locate the lock on to it's guide pins and with the key inserted maintain light inwards pressure, turn the key clockwise and engage the threaded spigot. Make sure that the lock is parallel and does not become cross threaded, it should turn easily, if there is any significant resistance do not force it but start again. Continue to turn the key clockwise maintaining inward pressure until the lock is screwed fully home, this will vary between 5 to 7 turns. Remove the key once the lock becomes firm enough **Do not over tighten** it is not necessary and does not improve the security. Check that the guard is a snug fit and seated correctly, it is at this juncture that the need for shaping will be apparent to achieve this. When fitted correctly the labia lips will be forced to protrude through the vaginal slot and will always be framed by it no matter what position is adopted.

Experience has shown that the FB/100 can be worn without any ill effects, some bruising may occur during the initial period of wear but this will soon pass. The use of talcum powder is recommended. The wearer will probably complain of all sorts of problems, but the only valid one is if the skin is broken and this must be treated seriously. The key-holder should be able to leave the FB/100 in place with confidence once fitted correctly.

The FB/100 will come to no harm if immersed in water, but in practice you will find that a shower is more

convenient than a bath. A detachable shower-head is ideal for washing out the guard while it is locked in position and negates the need to release it.

Note Radial locks are designed to operate dry. Do not lubricate with oil.