## PRIVATE AND CONFIDENTIAL MB/100 MEASUREMENT CHART

Customer:		
Date:		

<u>Important</u> it is essential that the measurements you record are as accurate as possible. A high degree of care and attention must be given to this task. Take plenty of time, repeating the measurement procedure until you are confident you are recording consistent and accurate values.

These ranges of belt sets are of a riveted construction and are not adjustable. Whilst small errors are not difficult to correct, major ones will invariably incur higher cost. An ordinary fabric or plastic tape measure of the type used for dressmaking is best for taking the measurements. You should aim at a tight rather than a loose fit, as experience shows a tight fit is far more comfortable than a loose one, which may also degrade effectiveness.

The subject should stand erect with their feet about 600mm apart and hands placed on back of their head while all the measurements are taken. These Belt sets are designed to fit into waist and cannot be worn on the hips like some fashionable jeans, trousers and skirts. The main reference point for all measurements is the bottom edge of the waistband, so it is of crucial importance that it is measured to fit the waist. For the person with a fuller or waistless figure, the Belt set will only be secure if the waistband is smaller than the circumference of the hips. Measurement M should be used to determine this, and the degree of discomfort that results. All measurements must be taken next to the skin.

	Description	cm
A	Waist normal	A =
В	Waist controlled ( take a deep breath and pull in to make it as small as possible)	B =
С	Penis length at full erection	C =
D	Penis length fully relaxed	D =
E	Penis circumference at full erection (mid point)	E =
F	Penis circumference fully relaxed (mid point)	F =
G	Waist to base of penis (top of )	G =
I	Waist front between legs to anus	I =
J	Waist front between legs and buttocks to rear waist	J =
K	Waist front between legs and over buttocks to rear waist	K =
L	Waist rear between buttocks to anus	L =
M	Waist measurement using 25mm wide belt.	M =
N	Hips circumference	N =
P	Body height.	P =

- **G.** Fasten around the waist a 25mm wide belt, from the bottom edge of the belt at front centre; measure down to the top of the base of the penis.
- I. From the same point, measure down between the legs to the anus; do not take the tape over the penis but to one side of it keeping as straight as possible. This is a very important measurement for the sake of accuracy it is worth repeating several times. The subject should maintain an upright position during this procedure. (do not bend over).
- J. With the belt still in position, find the centre back of the waist and mark it. Make a mark three 75mm to the right of it and a further 75mm to the left of it. By measuring from the centre back mark find the front centre of the waist and mark it. At the front centre, measure from the bottom edge of the belt down between the legs and up over the buttocks to the right hand mark at the rear waist; bottom edge. Repeat this procedure to the left-hand mark, this measurement should be the same and serves as double check.

Try to make sure the tape stays flat and in contact all the way, again do not measure over the penis but to either side keeping the tape as straight as possible. Exercise care with these measurements.

- **K.** With belt still in place, measure from the bottom edge front centre to bottom edge back centre. Make sure the tape fits snugly up between the buttocks, again not over the penis but to one side.
- L. Measure from the bottom edge centre back down to the anus, keeping the tape a snug fit between the buttocks.
- M. Adjust the belt to the smallest circumference at which you feel you could wear it and mark the position. Do not be tempted to settle for a nice comfortable fit, aim at a tight rather than a loose fit. Remove the belt, lay it out flat and measure from the end to the reference mark to determine the length. The waistband will be made to this measurement. A and B are used to provide a comparative check.

I certify that these measurements are correct.

Signed:		
~-8		

Quan- tity	Code	Product Description		Price	Sub To- tal
			SUB TOTAL =		
			CARRIAGE =		
			TOTAL =		
			DEPOSIT =		
			BALANCE =		

## ADDITIONAL ORDERING INFORMATION

 $\overline{\text{NP}/100}$  The standard plug measures 25mm diameter, length 115mm. If this is adequate for your requirements enter STD on the order form. Other size plugs can be made to order: our maximum machining limits are 64mm diameter, length 255mm). Indicate the size you require on the order form. For plugs over 38mm diameter and 150mm length, please add £5.00.

 $\underline{\text{NPS}/100}$  The standard shield plug measures 32mm diameter, length 140mm. If this is adequate for your requirements enter STD on the order form. Other size plugs can be made to order: our maximum machining limits are 64mm diameters, length 255mm. Indicate the size you require on the order form. For plugs over 38mm diameter and 150mm length, please add £5.00.

 $\underline{\mathbf{D}\text{-}\mathbf{RINGS}}$  Please indicate the locations of extra rings. (Please note, the front centre waist band location is  $\underline{\mathbf{not}}$  suitable for a ring.)

<u>Thigh Bands</u> The degree of restraint imposed by thigh bands is dictated to a large extent by the position they occupy and the links between them. The lower the position the more restrictive they become. On female belts it is better to have permanent links between the bands. For most purposes a 75mm linkage is adequate and quite practical. A separate chain loop and lock is available if preferred. Please indicate on order form P for permanent linkage and distance between bands, or CL for chain loop.

## MEASURING INSTRUCTIONS

With the belt still in position around the waist, fit another belt or similar around one of the thighs at the desired position (150mm above the knee is a typical choice, lower than this is not very practical).

Measure from the bottom edge of the waist belt at the side, down over the hip to the <u>top edge</u> of the thigh belt keeping the tape in contact to follow the hip profile. Mark the thigh belt before you remove it, lay it out flat and measure from the end to the reference mark to determine the circumference. Repeat this procedure with the other thigh in case there is any significant difference.

	Inches	cm
Right Thigh Circumference		
Left Thigh Circumference		
Side Chain Length		

	Ι	certify	that	these	measurements	are	correct.
--	---	---------	------	-------	--------------	-----	----------

Signed:	
Signed.	