

PRIVATE AND CONFIDENTIAL THIGH BAND MEASUREMENT CHART

Customer: _____

Date: _____

Important: thigh bands are supported by a waistband of some form either the waist band of a chastity belt or a plain belt dedicated to supporting the thigh bands. If you require the bands to be supported by a chastity belt please also use one of the chastity belt measuring charts. **Note the price of thigh bands does not include the cost of the supporting belt.** It is essential that the measurements you record are as accurate as possible. A high degree of care and attention must be given to this task. Take plenty of time, repeating the measurement procedure until you are confident you are recording consistent and accurate values.

These ranges of accessories are of a riveted construction and are not adjustable. Whilst small errors are not difficult to correct, major ones will invariably incur higher cost. An ordinary fabric or plastic tape measure of the type used for dressmaking is best for taking the measurements. You should aim at a tight rather than a loose fit, as experience shows a tight fit is far more comfortable and secure than a loose one.

The wearer should stand erect with their feet about twenty-four inches (60 cm) apart and hands placed on back of their head while all the measurements are taken. **These Belts are designed to fit into waist and cannot be worn on the hips like some fashionable jeans, trousers and skirts. The main reference point for all measurements is the bottom edge of the waistband, so it is of crucial importance that it is measured to fit the waist.**

For the person with a fuller or waistless figure, the Belt set will only be secure if the waistband is smaller than the circumference of the hips. Measurement M should be used to determine this, and the degree of discomfort that results. **All measurements must be taken next to the skin.**

The degree of restraint imposed by thigh bands is dictated to a large extent by the position they occupy and the links between them. The lower the position the more restrictive they become. On female belts it is better to have permanent links between the bands. For most purposes a maximum 3 inch (7.5 cm) spread of the legs is adequate and quite practical.

A separate chain loop and lock is available if preferred. Please indicate on order form P for permanent linkage and distance between bands, or CL for chain loop.

MEASURING INSTRUCTIONS

Fasten a belt (approximately 1 inch / 2.5 cm wide) around the waist. All Measurements must be taken from the bottom edge of the belt.

1. Make a mark (mark 1) on the body directly above the hip at the underside of the belt.
2. Make a mark (mark 2) directly under this one on the outside of the leg where you want the top of the thigh band, (6 inches (15 cm) above the knee is a typical choice, lower than this is not very practical).
3. Make a further two marks one $1\frac{1}{4}$ inches lower (mark 3) and one 4 inches higher (mark 4). (Thighs are tapered and the bands need to be as well for a better fit.)

With the belt still in position around the waist, fit another belt or similar around one of the thighs with the top of the belt on mark 2.

Measure from the bottom edge of the waist belt at the side (mark 1), down over the hip to the top edge of the thigh belt (mark 2) keeping the tape in contact to follow the hip profile. Mark the thigh belt before you remove it, lay it out flat and measure from the end to the reference mark to determine the circumference. Measure the circumference at marks 2 & 3. Repeat this procedure with the other thigh in case there is any significant difference.

Indicate Centimetres or Inches.

	Side chain	Circumference mark 2	Circumference mark 3	Circumference mark 4	Max spread of legs	Permanent connection
Left thigh						
Right thigh						

I certify that these measurements are correct. **Signed:** _____

Quantity	Code	Product Description	Price	Sub Total
SUB TOTAL =				
CARRIAGE =				
TOTAL =				
DEPOSIT =				
BALANCE =				